



### SPECIFICATIONS

CAPACITY . . . . .	3½" round or ¾" x 30" mild steel.
WEIGHT . . . . .	Approximately 16,000 pounds for bare shear, properly distributed at points of stress.
MOTOR AND DRIVE . . . . .	10 H.P., 220/440 v., 60 cy., 3 ph., A.C. at 1800 r.p.m. Drive is V-flat belts from grooved motor sheave to flat face flywheel.
CUTS PER MINUTE . . . . .	Thirty. The proper number for maximum production with safety to the operator.
KNIVES . . . . .	30" x 5" x 1¼". MOUNTED IN ADJUSTABLE KNIFE SEAT WHICH REQUIRES NO SHIMMING AFTER KNIVES HAVE BEEN SHARPENED.
JAW OPENING . . . . .	11½". Large enough for bulky material.
FLOOR SPACE . . . . .	Approximately 3' 6" x 11' 0".
BUSHINGS . . . . .	BRONZE BUSHED THROUGHOUT ON KING PIN, CRANKSHAFT, AND PITMAN ARM. ANTI-FRICTION BEARINGS ON FLYWHEEL SHAFT.
STYLE . . . . .	Right or left hand.

# GENSCO EQUIPMENT

53 Carlaw Ave., Toronto, Canada M4M 2R6 • Tel. 416-465-7521 • Telex: 065-24770

**SPECIALISTS IN SCRAP HANDLING AND PROCESSING EQUIPMENT**